



Datasheet

IP-20N

January 2025 | Rev. K

High-availability, split-mount, modular multicore aggregation node

The IP-20N is a highly-flexible aggregation node that delivers multi-Gbps radio capacity at a very large scale. Now available with multicore technology and new radio units, IP-20N features high modularity and flexibility and supports up to 8 radio links with an exceptionally wide variety of line interfaces via pluggable modules, in a wide range of network topologies - making it the preferred node for your transport network's aggregation sites.

The IP-20N operates within the entire microwave and millimeter-wave spectrum, offering high spectral efficiency across licensed and license-exempt frequency bands (4-86 GHz). It also supports all high-speed data interfaces (10G/1G/FE) and a wide variety of TDM interfaces (E1, STM-1); operates with a wide variety of multicore, standard and high power radios; and accommodates various network configurations including 1x 8+0, 4x 2+0, and 8x 1+0.

Note: For exact feature availability, contact your Ceragon representative. In case of discrepancy between this Datasheet and the Technical Description for the product, the Technical Description prevails.

General

Assembly options

1RU Chassis – 5x Universal slots;
2RU Chassis – 10x Universal slots
Redundant TCC slots (2RU chassis only)

Radio

Supported Frequency Range

Standard Power: 6-42 GHz
High Power: 4-11 GHz

Supported RFUs

RFU-D – High-capacity MultiCore radio
RFU-D-HP – High-capacity, high-power MultiCore radio
RFU-SX – High-capacity radio
RFU-C – High-capacity radio
1500HP/RFU-HP – High-capacity, high-power radio

Typical Radio Configurations

N+0 (up to N=8), 1x16+0, 1x 8+0, 2x 4+0, 4x 2+0, 8x 1+0, 1+1, 2+2
Split Mount (Standard Power, High Power)
All Indoor (High Power)

Radio Features

Layer 1 Link Bonding (up to 16+0)
Layer 1 Link Bonding with IP-50, IP-20, and third-party All-Outdoor Units
Multi-Carrier Adaptive Bandwidth Control (up to 8+0)
Protection and Diversity: HSB, SD (BBC and BBS)
High spectral utilization: BPSK to 4096 QAM w/ACM
Channel bandwidth: up to 112 MHz
XPIC
Multiband (with IP-50E/IP-20E)
Advanced Space Diversity (ASD)
Field Replaceable Diplexers/ Field Replaceable Channel Filters

Ethernet

Ethernet Interfaces

Up to 8 x 10/100Base-T (RJ-45)
Up to 10 x 1000Base-T (RJ-45)
Up to 2 x 2.5GBase-T (RJ-45)
Up to 14 x 1000Base-X (SFP)
Up to 8 x 10GBase-X (SFP+)
Management Interfaces - 2 x 10/100 Base-T (RJ-45)
SFP Types - Optical 1000Base-LX (1310 nm) or SX (850 nm)

Ethernet Features

MTU – 9600 Bytes

Quality of Service

- Multiple Classification criteria (VLAN ID, P-bits, IPv4 DSCP, IPv6 TC, MPLS EXP)
- 8 priority queues per port
- Deep buffering (configurable up to 64 Mbit per queue)
- WRED
- P-bit marking/remarking

4K VLANs

VLAN add/remove

MSTP, ERP (ITU-T G.8032)

Frame Cut Through – controlled latency and PDV for delay sensitive applications

Header DeDuplication – Capacity boosting by eliminating inefficiency in all layers (L2,MPLS, L3,L4, Tunneling – GTP for LTE, GRE)

Y.1731 Ethernet OAM

Y.1731 Ethernet Bandwidth Notification (ETH-BN)

TDM

TDM Interfaces

1RU Chassis: 80 x E1s; 5 x ch-STM-1s, 4 x STM-1s

2RU Chassis: 160 x E1s; 10 x ch-STM-1s, 8 x STM-1s

TDM Features

Native TDM services and TDM PWE using the same hardware

Integrated ch-STM-1 MUX (VC12)

XC capacity – 512 VCs

Timing options – Loop timing, system clock, recovered clock

1+1 / 1:1 path protection

Clear-channel STM-1 (RST)

Management Protocols

SNMP

REST

SDN Support:

- NETCONF/YANG

Synchronization

Synchronization Distribution

Sync Distribution over any traffic interface (GE/FE, E1, STM-1)

Dedicated In/Out synch interface (E1/2 MHz)

SyncE (ITU-T G.8261, G.8262)

SSM/ESMC Support for ring/mesh applications (ITU-T G.8264)

SyncE Regenerator mode, providing PRC grade (ITU-T G.811) performance for smart pipe applications

IEEE-1588

Optimized Transport for reduced PDV

IEEE-1588 TC

IEEE-1588 BC

Standards

MEF

Carrier Ethernet 2.0 (CE 2.0)

Supported Ethernet Standards

10/100/1000base-T/X (IEEE 802.3)

10G Base-LR (802.ae)

Ethernet VLANs (IEEE 802.3ac)

Virtual LAN (VLAN, IEEE 802.1Q)

Class of service (IEEE 802.1p)

Provider bridges (QinQ – IEEE 802.1ad)

Link aggregation (IEEE 802.3ad)

Auto MDI/MDIX for 1000baseT

RFC 1349: IPv4 TOS

RFC 2474: IPv4 DSCP

RFC 2460: IPv6 Traffic Classes

Supported E1 Standards

ITU-T G.703, G.736, G.775, G.823, G.824, G.828, ITU-T I.432, ETSI ETS 300 147, ETS 300 417

Supported STM-1 Standards

ITU-T G.703, G.775, G.813, G.825, EN 300 386 V1.2.1, ES 201 468; V1.1.1 :2000-03, ES 201 468 V1.2.1 :2002-09, EN 61000 4-3

TDM Pseudowire Standards

SAToP – RFC 4553

Security

Radio Encryption – AES 256

Secured protocols:

- HTTPS
- SNMPv3
- SSH
- SFTP

RADIUS authentication and authorization

TACACS+ Authentication, Authorization, and Accounting (session-based)

Standards Compliance

Radio Spectral Efficiency: EN 302 217-2

EMC: EN 301 489-4, EN 301 489-1, FCC 47 CFR, part 15, subpart B, ICES-003, TEC/SD/DD/EMC-221/05/OCT-16, IEC 61000-4-29

Safety: EN 62368-1, IEC 62368-1, UL 62368-1 CSA-C22.2 No.62368-1

Ingress Protection:

- RFU-D: IP67
- RFU-D-HP: IP67
- RFU-SX: IP67
- RFU-C: IP66
- 1500HP/RFU-HP: IP56

Storage: ETSI EN 300 019-1-1 Class 1.2

Transportation: ETSI EN 300 019-1-2 Class 2.3

Technical Specifications

RFU-HP (11 GHz) – Max Bias: 74W; Mid Bias: 64W;
Mute: 21W

1500HP – Max Bias: 85W; Mid Bias: 72W; Mute: 29W

Mechanical Specifications

1RU Chassis – 44.5mm(H), 444.3mm(W), 245mm(D), 3kg (empty);

2RU Chassis – 88mm(H), 444.3mm(W), 245mm(D), 6kg (empty)

Plugin Card Weights: 0.3kg – 1.5kg

RFU-D – 265mm(H), 230mm(W), 98mm(D), 5.22kg (includes diplexer unit)

RFU-D-HP – 358mm(H), 286mm(W), 107mm(D), 8.2kg (includes diplexer or OCU unit)

RFU-SX – 265mm(H), 230mm(W), 98mm(D), 5.22kg (includes diplexer unit)

RFU-C – 200mm(H), 200mm(W), 85mm(D), 4kg

1500HP/RFU-HP – 490mm(H), 144mm(W), 280mm(D), 7kg(W) (excluding Branching)

1500HP/RFU-HP OCB Branching (Split Mount and Compact All-Indoor) – 420mm(H), 110mm(W), 380mm(D), 7kg per carrier

Environmental Specifications

IDU:

- Continuous: -5° to +45°C
- Exceptional: -5° to +55°C

RFU: -33°C to +55°C

Power Input Specifications

IDU Standard Input: -48 VDC

IDU DC Input range: -40 to -60 VDC, with maximum current of up to 15A (1RU chassis) or 30A (2RU chassis)

Dual-feed power support

Power Consumption Specifications

TCC-B, TCC-B2, TCC-B-MC, and TCC-B2-XG-MC – 25W;
TCC-U – 45W; RMC – 17W; RIC-D – 12W; 1X10G LIC – 12W;
4XGE LIC – 9W; 16XE1 LIC – 17W; ch-STM-1 LIC – 25W;
STM-1 – 9W

Fans (1RU/2RU) – 6/30W max (4/6W-25°C)

RFU-D (2+0) – 6-11 GHz: 65W; 13-42 GHz: 48W

RFU-D-HP (2+0) – 135W*

RFU-D-HP (1+0 SD) – 88W*

RFU-D-HP (2+0 SD, Rx only) – 41W*

RFU-SX – 35W

RFU-C – 6-26 GHz (1+0/1+1): 22W/39W; 28-42 GHz (1+0/1+1): 26W/43W

RFU-HP (6-8 GHz) – Max Bias: 73W; Mid Bias: 48W; Min Bias: 34W; Mute: 18W

* For 80-112 MHz channels, an additional 6W can be expected.

Product Images

IDU

IP-20N 1RU CHASSIS



IP-20N 2RU CHASSIS



Modules

RADIO MODEM CARDS (RMCs)



RADIO INTERFACE CARDS (RICs)



TRAFFIC CONTROL CARDS (TCCs)



ETHERNET LIC WITH 1 COMBO AND 3 ELECTRICAL OR OPTICAL INTERFACES



ETHERNET LIC WITH A SINGLE 10G OPTICAL INTERFACE



TDM LICs



Radio Units

RFU-D



RFU-D-HP



RFU-SX



RFU-C



1500HP/RFU-HP



Radio Specifications

Capacity and Maximum Number of E1s

Notes: BPSK and 4096 QAM modulations require RFU-D, RFU-D-HP, or RFU-SX. For details about supported scripts, frequencies, and channels per RFU, refer to the Release Notes for the relevant CeraOS version.

	Capacity (Mbps)	Capacity De-Dup	Max. No. of E1s	Capacity (Mbps)	Capacity De-Dup	Max. No. of E1s	Capacity (Mbps)	Capacity De-Dup	Max. No. of E1s
Modulation	3.5 MHz			7 MHz			14 MHz		
BPSK	–	–	–	–	–	–	6-8	7-25	4
QPSK	3-4	4-13	2	8-10	9-32	3	17-20	17-63	8
8 QAM	–	–	–	13-16	13-48	5	26-32	28-100	12
16 QAM	8-10	9-32	4	18-22	19-69	8	38-46	39-143	17
32 QAM	11-14	12-43	5	24-30	26-92	10	50-62	53-192	23
64 QAM	14-17	15-54	6	30-37	32-114	112	63-77	66-238	28
128 QAM	17-21	18-65	7	36-44	38-137	15	76-93	80-290	33
256 QAM	19-24	20-74	8	42-51	44-158	17	87-107	92-333	38
512 QAM	–	–	–	45-54	47-169	18	97-119	102-369	42
1024 QAM Strong	–	–	–	48-58	50-182	19	103-126	108-391	45
1024 QAM Light	–	–	–	51-62	53-194	21	109-133	115-415	47
	28 MHz			40 MHz			56 MHz		
BPSK	18-22	19-68	9	26-31	27-97	12	40-49	42-153	18
QPSK	40-49	42-152	18	55-67	58-209	24	84-103	88-320	37
8 QAM	59-72	62-225	26	83-102	87-317	36	124-151	130-471	54
16 QAM	84-103	89-321	37	114-140	120-435	50	173-212	182-658	74
32 QAM	112-137	118-426	49	152-185	159-577	65	229-280	240-870	98
64 QAM	139-170	146-527	60	187-228	196-710	80	281-344	296-1071	120
128 QAM	167-205	176-637	72	227-277	238-862	97	341-416	358-1296	145
256 QAM	193-236	203-734	83	244-298	256-927	104	394-481	414-1498	168
512 QAM	206-251	216-782	88	267-327	281-1016	114	424-518	445-1612	180
1024 QAM Strong	225-274	236-854	96	303-371	319-1154	130	461-564	484-1754	196
1024 QAM Light	238-291	250-906	102	323-394	339-1227	138	490-599	515-1864	208
2048 QAM	260-318	273-989	111	349-427	367-1327	149	531-649	558-2020	226
4096 QAM	277-339	291-1055	118	369-451	388-1404	156	547-668	574-2079	232
	70 MHz			80 MHz			112 MHz		
BPSK	47-58	49-179	29	59-72	59-87	28	80-97	84-303	35
QPSK	97-119	102-369	58	122-149	123-180	57	163-200	172-622	70
8 QAM	139-170	146-528	83	174-213	175-257	80	244-299	256-929	104
16 QAM	199-244	209-758	118	245-299	247-362	113	333-407	350-1266	142
32 QAM	263-321	276-999	155	325-398	328-481	149	439-536	461-1669	187
64 QAM	322-393	338-1224	189	399-488	402-590	183	539-659	566-2051	229
128 QAM	381-465	400-1448	224	479-586	483-708	219	652-797	685-2481	277
256 QAM	439-537	461-1670	257	550-673	555-813	251	746-912	784-2500	317
512 QAM	482-590	507-1835	283	604-739	609-893	276	810-990	851-2500	344
1024 QAM Strong	525-642	552-1998	308	649-793	654-959	296	879-1075	923-2500	373
1024 QAM Light	558-682	586-2122	327	691-844	696-1021	315	933-1141	980-2500	396
2048 QAM	590-722	620-2246	346	731-894	737-1080	333	1007-1231	1057-2500	427

Transmit Power

RFU-D and RFU-SX

Modulation	Frequency (GHz)	6	7	8	11	13	15	18	23	26	28-32	38	42
BPSK - QPSK		28	28	28	28	24	24	22	22	21	18	22	15
8 QAM		28	28	28	28	24	24	22	22	21	18	22	15
16 QAM		28	27	27	28	23	24	22	22	20	17	21	15
32 QAM		28	27	26	28	23	24	22	22	19	16	21	14
64 QAM		28	26	26	27	23	24	22	22	19	16	20	13
128 QAM		27	26	26	26	22	24	22	22	19	16	20	13
256 QAM		27	26	26	26	21	22	20	22	17	14	19	13
512 QAM		27	25	24	26	21	22	20	21	17	14	19	11
1024 QAM		25	24	24	25	20	20	20	20	16	13	18	11
2048 QAM		25	23	22	24	20	20	18	19	15	12	18	10
4096 QAM		23	21	20	22	18	18	16					

RFU-D-HP

Modulation	Frequency (GHz)	4	5	6	7	8	10	11
BPSK		35	35	38	38	37	35	36
QPSK – 8 QAM		35	35	37	37	37	35	36
16 – 32 QAM		35	35	37	37	37	34	35
64 QAM		34	34	36	36	35	33	34
128 QAM		34	34	36	35	35	32	33
256 QAM		33	33	35	34	33	31	32
512 QAM		33	33	34	33	33	31	32
1024 QAM		32	32	33	32	32	30	31
2048 QAM		31	31	33	31	31	30	31
4096 QAM		30	30	31	29	29	28	29

RFU-C

Transmit Power	Frequency	6-8	11-15	18-23	24	26	28	36	38	42
QPSK/8 PSK		26	24	22	0	21	14	12	18	12
16 QAM		25	23	21	0	20	14	11	17	12
32 QAM		24	22	20	0	19	14	10	16	12
64 QAM		24	22	20	0	19	14	10	16	12
128 QAM		24	22	20	0	19	14	10	16	12
256 QAM		22	20	18	0	17	12	8	14	11
512 QAM		22	20	18	-1	17	9	10	14	11
1024 QAM		21	19	17	-3	16	8	9	13	10
2048 QAM		19	17	15	0	14	6	7	11	8

RFU-HP 1RX

Modulation	Frequency (GHz)	6L&H	7	8	11
QPSK – 16 QAM		33	33	33	30
32 QAM		33	33	33	29
64 QAM		32	32	32	29
128 QAM		31	31	31	29
256 QAM		30	30	30	27
512 QAM		28	28	28	25
1024 QAM		27	27	27	24
2048 QAM		25	25	25	22

RFU-HP 2RX (1500HP)

6L&H	7	8	11
33	33	33	30
33	33	33	29
32	32	32	29
32	32	32	29
30	30	30	27
28	28	28	25
27	27	27	24
25	25	25	22

Receiver Threshold (RSL)

Notes: BPSK and 4096 QAM modulations require RFU-D, RFU-D-HP, or RFU-SX.

RFU-D and RFU-SX

7 MHz	Frequency (GHz)	6	7-8	10	11	13	15	18	23	24	26	28-31	32	38	42
QPSK		-92.5	-92.0	-91.5	-92.5	-91.5	-90.5	-92.0	-91.0	-90.5	-90.5	-90.5	-90.0	-90.0	-89.5
8 PSK		-89.5	-89.0	-88.5	-89.5	-88.5	-87.5	-89.0	-88.0	-87.5	-87.5	-87.5	-87.0	-87.0	-86.5
16 QAM		-86.5	-86.0	-85.5	-86.5	-85.5	-84.5	-86.0	-85.0	-84.5	-84.5	-84.5	-84.0	-84.0	-83.5
32 QAM		-83.5	-82.5	-82.5	-83.5	-82.0	-81.5	-82.5	-82.0	-81.5	-81.5	-81.0	-81.0	-80.5	-80.0
64 QAM		-80.5	-79.5	-79.5	-80.0	-79.0	-78.5	-79.5	-79.0	-78.5	-78.5	-78.0	-78.0	-77.5	-77.0
128 QAM		-77.0	-76.5	-76.0	-77.0	-76.0	-75.0	-76.5	-75.5	-75.0	-75.0	-75.0	-74.5	-74.5	-74.0
256 QAM		-74.5	-73.5	-73.5	-74.0	-73.0	-72.5	-73.5	-72.5	-72.0	-72.5	-72.0	-72.0	-71.5	-71.0
512 QAM		-71.5	-71.0	-70.5	-71.5	-70.5	-69.5	-71.0	-70.0	-69.5	-69.5	-69.5	-69.0	-69.0	-68.5
1024 QAM Strong		-68.5	-68.0	-67.5	-68.5	-67.5	-66.5	-68.0	-67.0	-66.5	-66.5	-66.5	-66.0	-66.0	-65.5
1024 QAM Light		-68.0	-67.0	-67.0	-67.5	-66.5	-66.0	-67.0	-66.5	-66.0	-66.0	-65.5	-65.5	-65.0	-64.5
14 MHz															
BPSK		-91.5	-91.0	-90.5	-91.5	-90.5	-89.5	-91	-90.0	-89.5	-89.5	-89.5	-89.0	-89.0	-88.5
QPSK		-90.5	-90.0	-89.5	-90.5	-89.5	-88.5	-90	-89.0	-88.5	-88.5	-88.5	-88.0	-88.0	-87.5
8 PSK		-84.5	-84.0	-83.5	-85.5	-83.5	-82.5	-84	-83.0	-82.5	-82.5	-82.5	-82.0	-82.0	-81.5
16 QAM		-83.5	-83.0	-82.5	-83.5	-82.5	-81.5	-83	-82.0	-81.5	-81.5	-81.5	-81.0	-81.0	-80.5
32 QAM		-80.5	-79.5	-79.5	-80.5	-79.0	-78.5	-79.5	-79.0	-78.5	-78.5	-78.0	-78.0	-77.5	-77.0
64 QAM		-77.5	-76.5	-76.5	-77.0	-76.0	-75.5	-76.5	-76.0	-75.5	-75.5	-75.0	-75.0	-74.5	-74.0
128 QAM		-74.0	-73.5	-73.0	-74.0	-73.0	-72.0	-73.5	-72.5	-72.0	-72.0	-72.0	-71.5	-71.5	-71.0
256 QAM		-71.5	-70.5	-70.5	-71.0	-70.0	-69.5	-70.5	-69.5	-69.0	-69.5	-69.0	-69.0	-68.5	-68.0
512 QAM		-68.5	-68.0	-67.5	-68.5	-67.5	-66.5	-68.0	-67.0	-66.5	-66.5	-66.5	-66.0	-66.0	-65.5
1024 QAM Strong		-65.5	-65.0	-64.5	-65.5	-64.5	-63.5	-65.0	-64.0	-63.5	-63.5	-63.5	-63.0	-63.0	-62.5
1024 QAM Light		-65.0	-64.0	-64.0	-64.5	-63.5	-63.0	-64.0	-63.5	-63.0	-63.0	-62.5	-62.5	-62.0	-61.5
28 MHz															
BPSK		-88.5	-88.0	-87.5	-88.5	-87.5	-86.5	-88.0	-87.0	-86.5	-86.5	-86.5	-86.0	-86.0	-85.5
QPSK		-87.5	-87.0	-86.5	-87.5	-86.5	-85.5	-87.0	-86.0	-85.5	-85.5	-85.5	-85.0	-85.0	-84.5
8 PSK		-83.0	-82.5	-82.0	-83.0	-82.0	-81.0	-82.5	-81.5	-81.0	-81.0	-81.0	-80.5	-80.5	-80.0
16 QAM		-81.0	-80.5	-80.0	-81.0	-79.5	-79.0	-80.5	-79.5	-79.0	-79	-79.0	-78.5	-78.0	-78.0
32 QAM		-77.5	-77.0	-76.5	-77.5	-76.0	-75.5	-77.0	-76.0	-75.5	-75.5	-75.5	-75.0	-74.5	-74.5
64 QAM		-74.5	-74.0	-73.5	-74.5	-73.0	-72.5	-74.0	-73.0	-72.5	-72.5	-72.5	-72.0	-71.5	-71.5
128 QAM		-71.5	-70.5	-70.5	-71.0	-70.0	-69.5	-70.5	-69.5	-69.0	-69.5	-69.0	-69.0	-68.5	-68.0
256 QAM		-68.5	-67.5	-67.5	-68.0	-67.0	-66.5	-67.5	-66.5	-66.0	-66.5	-66.0	-66.0	-65.5	-65.0
512 QAM		-66.0	-65.0	-65.0	-66.0	-64.5	-64.0	-65.0	-64.5	-64.0	-64.0	-63.5	-63.5	-63.0	-62.5
1024 QAM Strong		-63.0	-62.5	-62.0	-63.0	-61.5	-61.0	-62.5	-61.5	-61.0	-61.0	-61.0	-60.5	-60.0	-60.0
1024 QAM Light		-62.0	-61.5	-61.0	-62.0	-60.5	-60.0	-61.5	-60.5	-60.0	-60.0	-60.0	-59.5	-59.0	-59.0
2048 QAM		-58.5	-58.0	-57.5	-58.5	-57.0	-56.5	-58.0	-57.0	-56.5	-56.5	-56.5	-56.0	-55.5	-55.5
4096 QAM		-55.5	-55.0	-54.5	-55.5	-54.0	-53.5	-55.0	-	-	-	-	-	-	-

40 MHz	Frequency (GHz)	6	7-8	10	11	13	15	18	23	24	26	28-31	32	38	42
BPSK		-87.0	-86.5	-86.0	-87.0	-86.0	-85.0	-86.5	-85.5	-85.0	-85.0	-85.0	-84.5	-84.5	-84.0
QPSK		-86.0	-85.5	-85.0	-86.0	-85.0	-84.0	-85.5	-84.5	-84.0	-84.0	-84.0	-83.5	-83.5	-83.0
8 PSK		-81.0	-80.5	-80.0	-81.0	-79.5	-79.0	-80.5	-79.5	-79.0	-79.0	-79.0	-78.5	-78.0	-78.0
16 QAM		-79.5	-79.0	-78.5	-79.5	-78.0	-77.5	-79.0	-78.0	-77.5	-77.5	-77.5	-77.0	-76.5	-76.5
32 QAM		-76.0	-75.0	-75.0	-75.5	-74.5	-74.0	-75.0	-74.0	-73.5	-74.0	-73.5	-73.5	-73.0	-72.5
64 QAM		-73.0	-72.0	-72.0	-73.0	-71.5	-71.0	-72.0	-71.5	-71.0	-71.0	-70.5	-70.5	-70.0	-69.5
128 QAM		-70.0	-69.0	-69.0	-70.0	-68.5	-68.0	-69.0	-68.5	-68.0	-68.0	-67.5	-67.5	-67.0	-66.5
256 QAM		-67.0	-66.0	-66.0	-66.5	-65.5	-65.0	-66.0	-65.0	-64.5	-65.0	-64.5	-64.5	-64.0	-63.5
512 QAM		-64.0	-63.5	-63.0	-64.0	-62.5	-62.0	-63.5	-62.5	-62.0	-62.0	-62.0	-61.5	-61.0	-61.0
1024 QAM Strong		-61.5	-61.0	-60.5	-61.5	-60.0	-59.5	-61.0	-60.0	-59.5	-59.5	-59.5	-59.0	-58.5	-58.5
1024 QAM Light		-60.5	-60.0	-59.5	-60.5	-59.5	-58.5	-60.0	-59.0	-58.5	-58.5	-58.5	-58.0	-58.0	-57.5
2048 QAM		-58.0	-57.0	-57.0	-58.0	-56.5	-56.0	-57.0	-56.5	-56.0	-56.0	-55.5	-55.5	-55.0	-54.5
4096 QAM		-55.0	-54.0	-54.0	-55.0	-53.5	-53.0	-54.0	-	-	-	-	-	-	-
56 MHz															
BPSK		-85.5	-85.0	-84.5	-85.5	-84.0	-83.5	-85.0	-84.0	-83.5	-83.5	-83.5	-83.0	-82.5	-82.5
QPSK		-84.5	-84.0	-83.5	-84.5	-83.0	-82.5	-84.0	-83.0	-82.5	-82.5	-82.5	-82.0	-81.5	-81.5
8 PSK		-80.0	-79.0	-79.0	-79.5	-78.5	-78.0	-79.0	-78.0	-77.5	-78.0	-77.5	-77.5	-77.0	-76.5
16 QAM		-77.5	-77.0	-76.5	-77.5	-76.0	-75.5	-77.0	-76.0	-75.5	-75.5	-75.5	-75.0	-74.5	-74.5
32 QAM		-74.0	-73.0	-73.0	-73.5	-72.5	-72.0	-73.0	-72.0	-71.5	-72.0	-71.5	-71.5	-71.0	-70.5
64 QAM		-70.5	-70.0	-69.5	-70.5	-69.5	-68.5	-70.0	-69.0	-68.5	-68.5	-68.5	-68.0	-68.0	-67.5
128 QAM		-68.0	-67.0	-67.0	-67.5	-66.5	-66.0	-67.0	-66.0	-65.5	-66.0	-65.5	-65.5	-65.0	-64.5
256 QAM		-64.5	-64.0	-63.5	-64.5	-63.5	-62.5	-64.0	-63.0	-62.5	-62.5	-62.5	-62.0	-62.0	-61.5
512 QAM		-62.5	-62.0	-61.5	-62.5	-61.5	-60.5	-62.0	-61.0	-60.5	-60.5	-60.5	-60.0	-60.0	-59.5
1024 QAM Strong		-59.0	-58.5	-58.0	-59.0	-58.0	-57.0	-58.5	-57.5	-57.0	-57.0	-57.0	-56.5	-56.5	-56.0
1024 QAM Light		-58.0	-57.5	-57.0	-58.0	-57.0	-56.0	-57.5	-56.5	-56.0	-56.0	-56.0	-55.5	-55.5	-55.0
2048 QAM		-55.5	-54.5	-54.5	-55.0	-54.0	-53.5	-54.5	-53.5	-53.0	-53.5	-53.0	-53.0	-52.5	-52.0
4096 QAM		-52.5	-51.5	-51.5	-52.0	-51.0	-50.5	-	-	-	-	-	-	-	-
70 MHz															
BPSK		-86.0	-86.0	-85.7	-86.6	-85.4	-84.7	-86.0	-85.1	-84.6	-84.7	-84.5	-84.2	-84.4	-83.5
QPSK		-83.2	-83.2	-82.9	-83.8	-82.6	-81.9	-83.2	-82.3	-81.8	-81.9	-81.7	-81.4	-81.6	-80.7
8 PSK		-79.5	-79.5	-79.2	-80.1	-78.9	-78.2	-79.5	-78.6	-78.1	-78.2	-78.0	-77.7	-77.9	-77.0
16 QAM		-76.5	-76.5	-76.2	-77.1	-75.9	-75.2	-76.5	-75.6	-75.1	-75.2	-75.0	-74.7	-74.9	-74.0
32 QAM		-72.9	-72.9	-72.6	-73.5	-72.3	-71.6	-72.9	-72.0	-71.5	-71.6	-71.4	-71.1	-71.3	-70.4
64 QAM		-70.0	-70.0	-69.7	-70.6	-69.4	-68.7	-70.0	-69.1	-68.6	-68.7	-68.5	-68.2	-68.4	-67.5
128 QAM		-67.2	-67.2	-66.9	-67.8	-66.6	-65.9	-67.2	-66.3	-65.8	-65.9	-65.7	-65.4	-65.6	-64.7
256 QAM		-64.4	-64.4	-64.1	-65.0	-63.8	-63.1	-64.4	-63.5	-63.0	-63.1	-62.9	-62.6	-62.8	-61.9
512 QAM		-61.7	-61.7	-61.4	-62.3	-61.1	-60.4	-61.7	-60.8	-60.3	-60.4	-60.2	-59.9	-60.1	-59.2
1024 QAM Strong		-58.8	-58.8	-58.5	-59.4	-58.2	-57.5	-58.8	-57.9	-57.4	-57.5	-57.3	-57.0	-57.2	-56.3
1024 QAM Light		-58.1	-58.1	-57.8	-58.7	-57.5	-56.8	-58.1	-57.2	-56.7	-56.8	-56.6	-56.3	-56.5	-55.6
2048 QAM		-55.9	-55.9	-55.6	-56.5	-55.3	-54.6	-55.9	-55.0	-54.5	-54.6	-54.4	-54.1	-54.3	-53.4

80 MHz	Frequency (GHz)	6	7-8	10	11	13	15	18	23	24	26	28-31	32	38	42
BPSK		-85.0	-85.0	-84.5	-85.5	-84.5	-83.5	-85.0	-84.0	-83.5	-83.5	-83.5	-83.0	-83.5	-82.5
QPSK		-82.5	-82.5	-82.5	-83.0	-82.0	-81.5	-82.5	-81.5	-81.0	-81.5	-81.0	-81.0	-81.0	-80.0
8 PSK		-79.0	-79.0	-78.5	-79.5	-78.5	-77.5	-79.0	-78.0	-77.5	-77.5	-77.5	-77.0	-77.5	-76.5
16 QAM		-76.0	-76.0	-75.5	-76.5	-75.0	-74.5	-76.0	-75.0	-74.5	-74.5	-74.5	-74.0	-74.0	-73.5
32 QAM		-72.5	-72.5	-72.0	-73.0	-71.5	-71.0	-72.5	-71.5	-71.0	-71.0	-71.0	-70.5	-70.5	-70.0
64 QAM		-69.0	-69.0	-69.0	-70.0	-68.5	-68.0	-69.0	-68.5	-68.0	-68.0	-67.5	-67.5	-67.5	-66.5
128 QAM		-66.5	-66.5	-66.0	-67.0	-66.0	-65.0	-66.5	-65.5	-65.0	-65.0	-65.0	-64.5	-65.0	-64.0
256 QAM		-63.5	-63.5	-63.0	-64.0	-63.0	-62.0	-63.5	-62.5	-62.0	-62.0	-62.0	-61.5	-62.0	-61.0
512 QAM		-61.0	-61.0	-61.0	-62.0	-60.5	-60.0	-61.0	-60.5	-60.0	-60.0	-59.5	-59.5	-59.5	-58.5
1024 QAM Strong		-58.0	-58.0	-57.5	-58.5	-57.5	-56.5	-58.0	-57.0	-56.5	-56.5	-56.5	-56.0	-56.5	-55.5
1024 QAM Light		-57.0	-57.0	-57.0	-58.0	-56.5	-56.0	-57.0	-56.5	-56.0	-56.0	-55.5	-55.5	-55.5	-54.5
2048 QAM		-54.5	-54.5	-54.5	-55.5	-54.0	-53.5	-54.5	-54.0	-53.5	-53.5	-53.0	-53.0	–	–
112 MHz															
BPSK		-82.0	-81.5	-81.0	-82.0	-80.5	-80.0	-81.5	-80.5	-80.0	-80.0	-80.0	-79.5	-79.0	-79.0
QPSK		-81.0	-80.5	-80.0	-81.0	-79.5	-79.0	-80.5	-79.5	-79.0	-79.0	-79.0	-78.5	-78.0	-78.0
8 PSK		-76.5	-75.5	-75.5	-76.0	-75.0	-74.5	-75.5	-74.5	-74.0	-74.5	-74.0	-74.0	-73.5	-73.0
16 QAM		-74.0	-73.5	-73.0	-74.0	-72.5	-72.0	-73.5	-72.5	-72.0	-72.0	-72.0	-71.5	-71.0	-71.0
32 QAM		-70.5	-69.5	-69.5	-70.0	-69.0	-68.5	-69.5	-68.5	-68.0	-68.5	-68.0	-68.0	-67.5	-67.0
64 QAM		-67.0	-66.5	-66.0	-67.0	-66.0	-65.0	-66.5	-65.5	-65.0	-65.0	-65.0	-64.5	-64.5	-64.0
128 QAM		-64.5	-63.5	-63.5	-64.0	-63.0	-62.5	-63.5	-62.5	-62.0	-62.5	-62.0	-62.0	-61.5	-61.0
256 QAM		-61.0	-60.5	-60.0	-61.0	-60.0	-59.0	-60.5	-59.5	-59.0	-59.0	-59.0	-58.5	-58.5	-58.0
512 QAM		-59.0	-58.5	-58.0	-59.0	-58.0	-57.0	-58.5	-57.5	-57.0	-57.0	-57.0	-56.5	-56.5	-56.0
1024 QAM Strong		-55.5	-55.0	-54.5	-55.5	-54.5	-53.5	-55.0	-54.0	-53.5	-53.5	-53.5	-53.0	-53.0	-52.5
1024 QAM Light		-54.5	-54.0	-53.5	-54.5	-53.5	-52.5	-54.0	-53.0	-52.5	-52.5	-52.5	-52.0	-52.0	-51.5
2048 QAM		-52.0	-51.0	-51.0	-51.5	-50.5	-50.0	-51.0	-50.0	-49.5	-49.5	-49.5	-49.5	–	–

RFU-D-HP

	7 MHz					14 MHz					28 MHz				
Frequency (GHz)	4-5	6	7	8	11	4-5	6	7	8	11	4-5	6	7	8	11
BPSK						-94.9	-94.6	-94.8	-94.2	-94.3	-91.9	-91.6	-91.8	-91.2	-91.3
QPSK	-94.0	-93.7	-93.9	-93.3	-93.4	-91.9	-91.6	-91.8	-91.2	-91.3	-88.9	-88.6	-88.8	-88.2	-88.3
8 PSK	-91.0	-90.7	-90.9	-90.3	-90.4	-88.0	-87.7	-87.9	-87.3	-87.4	-85.0	-84.7	-84.9	-84.3	-84.4
16 QAM	-88.0	-87.7	-87.9	-87.3	-87.4	-85.0	-84.7	-84.9	-84.3	-84.4	-82.0	-81.7	-81.9	-81.3	-81.4
32 QAM	-84.7	-84.4	-84.6	-84.0	-84.1	-81.7	-81.4	-81.6	-81.0	-81.1	-78.7	-78.4	-78.6	-78.0	-78.1
64 QAM	-81.7	-81.4	-81.6	-81.0	-81.1	-78.7	-78.4	-78.6	-78.0	-78.1	-75.7	-75.4	-75.6	-75.0	-75.1
128 QAM	-78.6	-78.3	-78.5	-77.9	-78.0	-75.6	-75.3	-75.5	-74.9	-75.0	-72.6	-72.3	-72.5	-71.9	-72.0
256 QAM	-75.5	-75.2	-75.4	-74.8	-74.9	-72.5	-72.2	-72.4	-71.8	-71.9	-69.5	-69.2	-69.4	-68.8	-68.9
512 QAM	-72.7	-72.4	-72.6	-72.0	-72.1	-69.7	-69.4	-69.6	-69.0	-69.1	-66.7	-66.4	-66.6	-66.0	-66.1
1024 QAM Strong	-69.8	-69.5	-69.7	-69.1	-69.2	-66.8	-66.5	-66.7	-66.1	-66.2	-63.8	-63.5	-63.7	-63.1	-63.2
1024 QAM Light	-69.1	-68.8	-69.0	-68.4	-68.5	-66.1	-65.8	-66.0	-65.4	-65.5	-63.1	-62.8	-63.0	-62.4	-62.5
2048 QAM											-60.6	-60.3	-60.5	-59.9	-60.0
4096 QAM											-56.6	-56.3	-56.5	-55.9	-56.0
	40 MHz					56 MHz					80 MHz				
Frequency (GHz)	4-5	6	7	8	11	4-5	6	7	8	11	4-5	6	7	8	11
BPSK	-90.6	-90.3	-90.5	-89.9	-90.0	-89.1	-88.8	-89.0	-88.4	-88.5	-86.8	-86.5	-86.7	-86.1	-86.2
QPSK	-87.4	-87.1	-87.3	-86.7	-86.8	-85.9	-85.6	-85.8	-85.2	-85.3	-84.5	-84.2	-84.4	-83.8	-83.9
8 PSK	-83.4	-83.1	-83.3	-82.7	-82.8	-81.8	-81.5	-81.7	-81.1	-81.2	-80.8	-80.5	-80.7	-80.1	-80.2
16 QAM	-80.5	-80.2	-80.4	-79.8	-79.9	-78.9	-78.6	-78.8	-78.2	-78.3	-77.8	-77.5	-77.7	-77.1	-77.2
32 QAM	-77.1	-76.8	-77.0	-76.4	-76.5	-75.6	-75.3	-75.5	-74.9	-75	-74.4	-74.1	-74.3	-73.7	-73.8
64 QAM	-74.0	-73.7	-73.9	-73.3	-73.4	-72.6	-72.3	-72.5	-71.9	-72.0	-71.5	-71.2	-71.4	-70.8	-70.9
128 QAM	-71.0	-70.7	-70.9	-70.3	-70.4	-69.7	-69.4	-69.6	-69.0	-69.1	-68.5	-68.2	-68.4	-67.8	-67.9
256 QAM	-68.7	-68.4	-68.6	-68.0	-68.1	-66.5	-66.2	-66.4	-65.8	-65.9	-65.8	-65.5	-65.7	-65.1	-65.2
512 QAM	-65.9	-65.6	-65.8	-65.2	-65.3	-63.9	-63.6	-63.8	-63.2	-63.3	-63.1	-62.8	-63.0	-62.4	-62.5
1024 QAM Strong	-62.4	-62.1	-62.3	-61.7	-61.8	-60.6	-60.3	-60.5	-59.9	-60.0	-59.9	-59.6	-59.8	-59.2	-59.3
1024 QAM Light	-61.7	-61.4	-61.6	-61.0	-61.1	-59.7	-59.4	-59.6	-59.0	-59.1	-59.5	-59.2	-59.4	-58.8	-58.9
2048 QAM	-59.4	-59.1	-59.3	-58.7	-58.8	-57.9	-57.6	-57.8	-57.2	-57.3	-56.6	-56.3	-56.5	-55.9	-56.0
4096 QAM	-56.3	-56.0	-56.2	-55.6	-55.7	-54.0	-53.7	-53.9	-53.3	-53.4					
	112 MHz														
Frequency (GHz)	4-5	6	7	8	11										
BPSK	-85.4	-85.1	-85.3	-84.7	-84.8										
QPSK	-83.0	-82.7	-82.9	-82.3	-82.4										
8 PSK	-79.0	-78.7	-78.9	-78.3	-78.4										
16 QAM	-76.1	-75.8	-76.0	-75.4	-75.5										
32 QAM	-72.7	-72.4	-72.6	-72.0	-72.1										
64 QAM	-69.7	-69.4	-69.6	-69.0	-69.1										
128 QAM	-66.8	-66.5	-66.7	-66.1	-66.2										
256 QAM	-63.8	-63.5	-63.7	-63.1	-63.2										
512 QAM	-61.4	-61.1	-61.3	-60.7	-60.8										
1024 QAM Strong	-58.4	-58.1	-58.3	-57.7	-57.8										
1024 QAM Light	-57.7	-57.4	-57.6	-57.0	-57.1										
2048 QAM	-55.1	-54.8	-55.0	-54.4	-54.5										

RFU-C

3.5 MHz	Frequency (GHz)	6	7-10	11-15	18	23	24	26	28	31-42
QPSK		-98.0	-97.5	-98.0	-97.0	-96.5	-93.5	-95.5	-93.5	-94.5
16 QAM		-91.0	-90.5	-91.0	-90.0	-89.5	-86.5	-88.5	-86.5	-87.5
32 QAM		-87.5	-87.0	-87.5	-86.5	-86.0	-83.0	-85.0	-83.0	-84.0
64 QAM		-84.5	-84.0	-84.5	-83.5	-83.0	-80.0	-82.0	-80.0	-81.0
128 QAM		-80.5	-80.0	-80.5	-79.5	-79.0	-76.0	-78.0	-76.0	-77.0
256 QAM		-77.5	-77.0	-77.5	-76.5	-76.0	-73.0	-75.0	-73.0	-74.0
7 MHz										
QPSK		-95.0	-94.5	-95.0	-94.0	-93.5	-90.5	-92.5	-90.5	-91.5
8 PSK		-90.0	-89.5	-90.0	-89.0	-88.5	-85.5	-87.5	-85.5	-86.5
16 QAM		-88.5	-88.0	-88.5	-87.5	-87.0	-84.0	-86.0	-84.0	-85.0
32 QAM		-85.0	-84.5	-85.0	-84.0	-83.5	-80.5	-82.5	-80.5	-81.5
64 QAM		-82.0	-81.5	-82.0	-81.0	-80.5	-77.5	-79.5	-77.5	-78.5
128 QAM		-78.5	-78.0	-78.5	-77.5	-77.0	-74.0	-76.0	-74.0	-75.0
256 QAM		-75.0	-74.5	-75.0	-74.0	-73.5	-70.5	-72.5	-70.5	-71.5
512 QAM		-73.0	-72.5	-73.0	-72.0	-71.5	-68.5	-70.5	-68.5	-69.5
1024 QAM Strong		-69.5	-69.0	-69.5	-68.5	-68.0	-65.0	-67.0	-65.0	-66.0
1024 QAM Light		-68.5	-68.0	-68.5	-67.5	-67.0	-64.0	-66.0	-64.0	-65.0
14 MHz										
QPSK		-92.0	-91.5	-92.0	-91.0	-90.5	-87.5	-89.5	-87.5	-88.5
8 PSK		-87.0	-86.5	-87.0	-86.0	-85.5	-82.5	-84.5	-82.5	-83.5
16 QAM		-85.5	-85.0	-85.5	-84.5	-84.0	-81.0	-83.0	-81.0	-82.0
32 QAM		-82.0	-81.5	-82.0	-81.0	-80.5	-77.5	-79.5	-77.5	-78.5
64 QAM		-78.5	-78.0	-78.5	-77.5	-77.0	-74.0	-76.0	-74.0	-75.0
128 QAM		-75.5	-75.0	-75.5	-74.5	-74.0	-71.0	-73.0	-71.0	-72.0
256 QAM		-72.5	-72.0	-72.5	-71.5	-71.0	-68.0	-70.0	-68.0	-69.0
512 QAM		-69.5	-69.0	-69.5	-68.5	-68.0	-65.0	-67.0	-65.0	-66.0
1024 QAM Strong		-66.5	-66.0	-66.5	-65.5	-65.0	-62.0	-64.0	-62.0	-63.0
1024 QAM Light		-65.5	-65.0	-65.5	-64.5	-64.0	-61.0	-63.0	-61.0	-62.0
28 MHz										
QPSK		-89.0	-88.5	-89.0	-88.0	-87.5	-84.5	-86.5	-84.5	-85.5
8 PSK		-84.0	-83.5	-84.0	-83.0	-82.5	-79.5	-81.5	-79.5	-80.5
16 QAM		-82.5	-82.0	-82.5	-81.5	-81.0	-78.0	-80.0	-78.0	-79.0
32 QAM		-79.0	-78.5	-79.0	-78.0	-77.5	-74.5	-76.5	-74.5	-75.5
64 QAM		-76.0	-75.5	-76.0	-75.0	-74.5	-71.5	-73.5	-71.5	-72.5
128 QAM		-73.0	-72.5	-73.0	-72.0	-71.5	-68.5	-70.5	-68.5	-69.5
256 QAM		-70.0	-69.5	-70.0	-69.0	-68.5	-65.5	-67.5	-65.5	-66.5
512 QAM		-67.0	-66.5	-67.0	-66.0	-65.5	-62.5	-64.5	-62.5	-63.5
1024 QAM Strong		-64.0	-63.5	-64.0	-63.0	-62.5	-59.5	-61.5	-59.5	-60.5
1024 QAM Light		-63.5	-63.0	-63.5	-62.5	-62.0	-59.0	-61.0	-59.0	-60.0
2048 QAM		-60.5	-60.0	-60.5	-59.5	-59.0	-56.0	-58.0	-56.0	-57.0

40 MHz	Frequency	6	7-10	11-15	18	23	24	26	28	31-42
QPSK		-88.0	-87.5	-88.0	-87.0	-86.5	-83.5	-85.5	-83.5	-84.5
8 PSK		-82.5	-82.0	-82.5	-81.5	-81.0	-78.0	-80.0	-78.0	-79.0
16 QAM		-81.0	-80.5	-81.0	-80.0	-79.5	-76.5	-78.5	-76.5	-77.5
32 QAM		-77.5	-77.0	-77.5	-76.5	-76.0	-73.0	-75.0	-73.0	-74.0
64 QAM		-74.5	-74.0	-74.5	-73.5	-73.0	-70.0	-72.0	-70.0	-71.0
128 QAM		-71.5	-71.0	-71.5	-70.5	-70.0	-67.0	-69.0	-67.0	-68.0
256 QAM		-69.0	-68.5	-69.0	-68.0	-67.5	-64.5	-66.5	-64.5	-65.5
512 QAM		-66.5	-66.0	-66.5	-65.5	-65.0	-62.0	-64.0	-62.0	-63.0
1024 QAM Strong		-63.0	-62.5	-63.0	-62.0	-61.5	-58.5	-60.5	-58.5	-59.5
1024 QAM Light		-62.0	-61.5	-62.0	-61.0	-60.5	-57.5	-59.5	-57.5	-58.5
2048 QAM		-59.0	-58.5	-59.0	-58.0	-57.5	-54.5	-56.5	-54.5	-55.5
56 MHz										
QPSK		-86.0	-85.5	-86.0	-85.0	-84.5	-81.5	-83.5	-81.5	-82.5
8 PSK		-81.0	-80.5	-81.0	-80.0	-79.5	-76.5	-78.5	-76.5	-77.5
16 QAM		-79.0	-78.5	-79.0	-78.0	-77.5	-74.5	-76.5	-74.5	-75.5
32 QAM		-76.0	-75.5	-76.0	-75.0	-74.5	-71.5	-73.5	-71.5	-72.5
64 QAM		-72.5	-72.0	-72.5	-71.5	-71.0	-68.0	-70.0	-68.0	-69.0
128 QAM		-70.0	-69.5	-70.0	-69.0	-68.5	-65.5	-67.5	-65.5	-66.5
256 QAM		-67.0	-66.5	-67.0	-66.0	-65.5	-62.5	-64.5	-62.5	-63.5
512 QAM		-64.5	-64.0	-64.5	-63.5	-63.0	-60.0	-62.0	-60.0	-61.0
1024 QAM Strong		-61.0	-60.5	-61.0	-60.0	-59.5	-56.5	-58.5	-56.5	-57.5
1024 QAM Light		-60.5	-60.0	-60.5	-59.5	-59.0	-56.0	-58.0	-56.0	-57.0
2048 QAM		-58.0	-57.5	-58.0	-57.0	-56.5	-53.5	-55.5	-53.5	-54.5

RFU-HP

	14 MHz		28 MHz		40 MHz		56 MHz	
Frequency (GHz)	6 GHz	7-11 GHz	6 GHz	7-11 GHz	6 GHz	7-11 GHz	6 GHz	7-11 GHz
QPSK	-91.5	-91.0	-88.5	-88.0	-87.0	-86.5	-85.5	-85.0
8 PSK	-86.5	-86.0	-83.5	-83.0	-82.0	-81.5	-80.5	-80.0
16 QAM	-85.0	-84.5	-82	-81.5	-80.5	-80.0	-79.0	-78.5
32 QAM	-81.5	-81.0	-78.5	-78.0	-77.0	-76.5	-75.5	-75.0
64 QAM	-78.5	-78.0	-75.5	-75.0	-74.0	-73.5	-72.0	-71.5
128 QAM	-75.0	-74.5	-72.5	-72.0	-71.0	-70.5	-69.5	-69.0
256 QAM	-72.0	-71.5	-69.5	-69.0	-68.5	-68.0	-66.5	-66.0
512 QAM	-69.5	-69.0	-67	-66.5	-66.0	-65.5	-64.0	-63.5
1024 QAM Strong	-66.5	-66.0	-64	-63.5	-63.0	-62.5	-61.0	-60.5
1024 QAM Light	-65.5	-65.0	-63.5	-63.0	-62.0	-61.5	-60.0	-59.5
2048 QAM	—	—	-59.5	-59.0	-58.5	-58.0	-56.5	-56.0

1500HP

	14 MHz		28 MHz		40 MHz	
Frequency (GHz)	6 GHz	7-11 GHz	6 GHz	7-11 GHz	6 GHz	7-11 GHz
QPSK	-91.0	-91.0	-88.0	-88.0	-86.5	-86.5
8 PSK	-86.0	-86.0	-83.0	-83.0	-81.5	-81.5
16 QAM	-84.5	-84.5	-81.5	-81.5	-80.0	-80.0
32 QAM	-81.0	-81.0	-78.0	-78.0	-76.5	-76.5
64 QAM	-78.0	-78.0	-75.0	-75.0	-73.5	-73.5
128 QAM	-74.5	-74.5	-72.0	-72.0	-70.5	-70.5
256 QAM	-71.5	-71.5	-69.0	-69.0	-68.0	-68.0
512 QAM	-69.0	-69.0	-66.5	-66.5	-65.5	-65.5
1024 QAM Strong	-66.0	-66.0	-63.5	-63.5	-62.5	-62.5
1024 QAM Light	-65.0	-65.0	-63.0	-63.0	-61.5	-61.5
2048 QAM	–	–	-59.0	-59.0	-58.0	-58.0

Note: Feature availability and specifications are subject to change without prior notification.