



## MULTIHAUL™ TG N367

### Scalable 360° Fixed Wireless Access Distribution Node

The MultiHaul™ TG system marks the release of the Siklu-by-Ceragon 3<sup>rd</sup> generation point to multipoint 60GHz products, with Terragraph certification. The solution consists of Distribution Nodes (DN) operating over millimeter waves in a redundant mesh topology which connect a suite of Customer-Nodes (CN). The MultiHaul™ TG family of products brings the advantages of mmWave spectrum – multi-gigabit capacity, immunity to interference and massive amounts of available spectrum - to an easy to deploy solution with the addition of L2 SDN mesh, enabled by the Ceragon NMS with the Runner subsystem, for stress-free coverage extension and multi-path reliability. The N367's advanced capabilities, including support for up to 60 CN links, self-backhaul, and meshing, make it highly scalable and flexible for deployments in diverse environments, from neighborhoods to business districts.

#### Enhanced RF2 antennas, High Capacity and Flexibility for Dense Deployments

The MultiHaul™ TG Nodes operate with 4 independent sectors over the millimeter wave spectrum using narrow beams. This confers several advantages including multi-gigabit capacity in dense deployments. With 4 independent high-gain beam-forming RF2 antennas, a multitude of network topologies can be realized to optimize coverage, capacity, and performance. The industry unique RF2 antennas deliver a superior link budget, enhancing the service capacity and availability across a 60% to 80% larger service area, compared to non RF2 antennas.

#### A Wide Range of Applications

- Fixed 5G Wireless Access, Gigabit to the Home, the MDU and the Enterprise
- Wi-Fi Hotspot Backhaul
- Security / Safe City Networks
- Smart City Business Services, Municipal networks
- Small Cell Backhaul

#### Always-On Mission Critical Networks

When you can't afford to lose a video stream, critical safe city sensor data or any other mission critical data, you need a wireless network that's as reliable and secure as fiber. With maximal immunity to interference and hacker-proof links with embedded AES encryption, MultiHaul™ TG delivers a network you can count on. An additional layer of reliability is available through the L2 self-organizing (SON) capabilities enabled by Ceragon NMS with Runner, enabling automatic reorganization and rerouting around site failures.

#### Integrated Future-Safe Multi-Functional Node

Wireless infrastructure should be simple, and future proof. Organizations want to quickly deploy a single box across the target neighborhood, knowing that this infrastructure will address the needs of self-backhaul, distribution, local services, redundancy, SLA enforcement, with enough horsepower to scale the bandwidth and accommodate new features over the foreseeable future, achieving a long and useful lifetime.

#### Fiber Quality with Wireless Flexibility

The Siklu-by-Ceragon millimeter wave radios successfully combine the capacity of fiber with the flexibility, speed of deployment and low TCO of wireless networks. That is what makes them the world's best-selling millimeter wave radios every year since 2011. They provide rock solid performance, even in very dense networks or under severe weather conditions, in thousands of networks around the globe.

#### Highly Secure and Physically Immune Beams

The narrow beamwidth confers several advantages including immunity to interference and network jamming. In contrast to wide-beam wireless systems that need to use multiple strategies to perform in dense areas. Multiple CNs and services can be served with complete isolation based on physical port, VLAN ID and/or a CN.

#### Ready Set Go

The plug and play integrated node is designed for an easy single person installation. The advanced scanning antennas automatically aligns with other Nodes or with Customer-Nodes. For buildings with difficult roof-top access, a single Node is installed on its roof to serve multiple locations.



# MULTIHAUL™ TG NODE - N367

## 60GHz 4x RF2 Sectors Wireless L2 Mesh Node Specifications

<b>Topologies</b>	Point to Point, Point to Multi-point, Self-Backhaul L2 SDN Mesh.
<b>Frequency &amp; Duplexing</b>	57-66GHz, TDD/TDMA. 4 channels, IEEE 802.11ay.
<b>Channel Bandwidth, Modulation &amp; Adaptive Coding, TPC</b>	2,160MHz, BPSK to QAM16, up to 10 levels of hitless adaptive bandwidth, coding, and modulation – boost gain by over 29dB. Automatic Transmit Power Control (ATPC), per link.
<b>Radio OTA Rate (over the air) / Throughput</b>	OTA up to 4,600 Mbps per sector, Throughput > 1,900 Mbps full duplex per sector (> 7.6 Gbps full duplex per node)
<b>System Gain (link budget)</b>	RF2 enabled, up to 128.5dB (Distribution Node to Customer-Node, including RF2 antenna gain). Please refer to the Siklu-by-Ceragon SmartHaul™ Link Budget Calculator ( <a href="http://lbc.siklu.com">lbc.siklu.com</a> ) for radio link performance models.
<b>Sector(s)</b>	4x 90° sector, for 360° coverage, any sector on any channel. Horizontal scanning: 90° per sector. Vertical scanning: 25°.
<b>Network Synchronization</b>	On-board GPS enabling multi node co-location
<b>Interfaces</b>	3 ports: 1x RJ-45 10/5/2.5/1GbE with PoE-In, 1x RJ-45 1GbE with PoE-Out (42W), 1x SFP+ 10GbE.
<b>Ethernet Features</b>	IEEE 802.1d transparent bridging, IEEE 802.1q Virtual LAN, IEEE 802.1ad Provider bridge VLAN stacking.
<b>Security</b>	AES 128-bits OTA, GUI over HTTPS, CLI over SSH.
<b>Management &amp; Provisioning</b>	In-band, Out-of-band management, Web GUI (one-pane configuration of local and remote units) & Embedded CLI, NETCONF, SNMP.
<b>PoE-Out</b>	1 port, 42W POE-Out (IEEE 802.3bt; cable loss may affect power delivered to the PD).
<b>Power Supply</b>	PoE-In (IEEE 802.3bt or passive), or 48V DC (via RJ-45 adaptor) 48W no POE-Out, 90W with 42W POE-Out.
<b>Conformance</b>	Radio: US FCC 47 CFR Part 15.255; EN 303 722; UK IR 2030 EMC: US FCC 47 CFR Part 15; EN 301 489, Safety: UL/IEC 62368-1; UL/IEC 60950-22.
<b>Terragraph</b>	Terragraph Certified.
<b>Environmental</b>	Operating Temperature: -49° ÷ +131°F (-45° ÷ +55°C); Ingress Protection Rating: IP67.
<b>Dimensions</b>	7.7 x 9.5 x 7.2 in. / 195 x 242 x 184 mm (width x height x depth)
<b>Weight</b>	7.9 lbs. / 3.6 Kg.

## Ordering Information

<b>MH-N367-CCP-PoE-MWB</b>	MultiHaul™ TG Enhanced Node, 360°, 7.2 Gbps, 1 RJ-45 10GE & 1 RJ-45 1GE & 1 SFP+ 10GE, mounting kit and metallic bands, all weather shells, grounding cable, quick start guide (QSG). IP-67, White.
<b>AX-MK-N36x-45</b>	Mounting Kit for N36x, rotated 45°

Rev A5 d3